

# Construction

## PROFESSIONAL GRADE FEATURES



**ADJUSTABLE SOLID RUBBER HOSE STOP**  
for lead length positioning

**VERSATILE GUIDE ARM** adjusts to wall,  
floor, ceiling & vehicle mounting

**EXTERNAL FLUID PATH WITH FULL-FLOW  
BRASS NPT SWIVEL** that screws directly on  
1" solid steel axle, for simple seal maintenance  
and fast and easy hose installation  
*- Viewable on opposite side*

**HIGH QUALITY STEEL CONSTRUCTION** with our  
durable CPC™ powder coat finish

**HEAVY DUTY SPUN DISCS WITH ROLLED EDGES**  
- not stamped, for greater strength, made with  
first of its kind CNC robotic spinning cell

**ENCLOSED FACTORY TUNED AND MATCHED  
CARTRIDGE-STYLE SPRING MOTOR**, easily  
removed for safe & convenient replacement  
*- Viewable on opposite side*

**HEAVY GAUGE 1/4" STAINLESS STEEL BASE  
& SUPPORT POST** for maximum stability

**TRIPLE AXLE SUPPORT WITH SUPER HUB™  
& A FULL FRAME** increased reel strength  
for more demanding applications  
*Only on T Series. SH Series features dual axle support*

## POSSIBLE FIELDS OF APPLICATION

- Pneumatic Tools
- Washdown
- Ground Maintenance
- Lubrication
- Power Tools
- Welding
- Water Trucks
- High Volume Delivery

[www.coxreels.com](http://www.coxreels.com)

800.COX.REEL

P: 480.820.6396

F: 480.820.5132

E: [info@coxreels.com](mailto:info@coxreels.com)





## SH, MP & HP SERIES - EQUIPPED WITH SUPER HUB™

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- Sturdy single pedestal spring driven reel features Coxreels' exclusive Super Hub™ dual axle support system



| MODEL    | EZ-Coil® Safety Line | I.D. | FT. | PSI   | APRX. LBS. | W x H x L                |
|----------|----------------------|------|-----|-------|------------|--------------------------|
| SH-N-350 | EZ-SH-350            | 3/8" | 50  | 300   | 50         | 8 1/4 x 21 1/4 x 19 1/2" |
| SH-N-450 | EZ-SH-450            | 1/2" | 50  | 300   | 54         | 8 1/4 x 21 1/4 x 19 1/2" |
| MP-N-350 | EZ-MP-350            | 3/8" | 50  | 3,000 | 65         | 8 1/4 x 21 1/4 x 19 1/2" |
| MP-N-450 | EZ-MP-450            | 1/2" | 50  | 2,500 | 67         | 8 3/4 x 25 1/2 x 19 1/2" |
| HP-N-150 | EZ-HP-150            | 1/4" | 50  | 5,000 | 64         | 8 3/4 x 25 1/2 x 19 1/2" |
| HP-N-350 | EZ-HP-350            | 3/8" | 50  | 4,000 | 65         | 9 1/4 x 25 1/2 x 19 1/2" |



## T SERIES - EQUIPPED WITH SUPER HUB™

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- Sturdy dual pedestal reel features Coxreels' exclusive Super Hub™ dual axle support system



| MODEL      | EZ-Coil® Safety Line | I.D. | FT. | PSI | APRX. LBS. | W x H x L                |
|------------|----------------------|------|-----|-----|------------|--------------------------|
| TSH-N-350  | EZ-TSH-350           | 3/8" | 50  | 300 | 61         | 9 3/8 x 21 1/4 x 19 1/2" |
| TSH-N-3100 | EZ-TSH-3100          | 3/8" | 100 | 300 | 85         | 9 3/8 x 25 1/2 x 24"     |
| TSH-N-450  | EZ-TSH-450           | 1/2" | 50  | 300 | 63         | 9 3/8 x 21 1/4 x 19 1/2" |
| TSH-N-4100 | EZ-TSH-4100          | 1/2" | 100 | 300 | 95         | 9 3/8 x 25 1/2 x 24"     |
| TSH-N-550  | EZ-TSH-550           | 3/4" | 50  | 300 | 83         | 9 7/8 x 25 1/2 x 24"     |
| TSH-N-650  | -                    | 1"   | 50  | 300 | 98         | 12 x 25 1/2 x 24"        |



## DUAL HYDRAULIC

- External fluid path with dual port melanzed 90° full-flow NPT swivel inlet
- Swivel Seals: TEFLON

| MEDIUM PRESSURE |            |      |     |       |     |                          |
|-----------------|------------|------|-----|-------|-----|--------------------------|
| TMP-N-350       | EZ-TMP-350 | 3/8" | 50  | 3,000 | 74  | 9 3/8 x 21 1/4 x 19 1/2" |
| TMP-N-3100      | -          | 3/8" | 100 | 3,000 | 106 | 9 3/8 x 25 1/2 x 24"     |
| TMP-N-450       | EZ-TMP-450 | 1/2" | 50  | 2,500 | 77  | 9 3/8 x 21 1/4 x 19 1/2" |
| TMP-N-4100      | -          | 1/2" | 100 | 2,500 | 106 | 9 3/8 x 25 1/2 x 24"     |

| HIGH PRESSURE |             |      |     |       |     |                          |
|---------------|-------------|------|-----|-------|-----|--------------------------|
| THP-N-150     | EZ-THP-150  | 1/4" | 50  | 5,000 | 74  | 9 3/8 x 21 1/4 x 19 1/2" |
| THP-N-1100    | EZ-THP-1100 | 1/4" | 100 | 5,000 | 104 | 9 3/8 x 25 1/2 x 24"     |
| THP-N-350     | EZ-THP-350  | 3/8" | 50  | 4,000 | 78  | 9 3/8 x 21 1/4 x 19 1/2" |
| THP-N-375     | EZ-THP-375  | 3/8" | 75  | 4,000 | 98  | 9 3/8 x 25 1/2 x 24"     |

| DUAL HYDRAULIC |   |      |    |       |     |                       |
|----------------|---|------|----|-------|-----|-----------------------|
| TDMP-N-350     | - | 3/8" | 50 | 3,000 | 104 | 11 3/8 x 25 1/2 x 24" |
| TDMP-N-450     | - | 1/2" | 50 | 2,500 | 106 | 11 3/8 x 25 1/2 x 24" |



## PC SERIES

- External heavy gauge CPC™ powder coated steel component cover for simple slip ring routine maintenance
- Single pedestal cord reel with space saving design facilitates workplace organization
- Choice of electrical accessories



| MODEL       | EZ-Coil® Safety Line | ACCESSORY           | AWG / NO. COND. | CORD FT. | AMPS | APRX. LBS. | W x H x L                |
|-------------|----------------------|---------------------|-----------------|----------|------|------------|--------------------------|
| PC13-5012-A | EZ-PC13-5012-A       | Single receptacle   | 12 / 3          | 50       | 20   | 40         | 8 1/2 x 14 7/8 x 13 1/2" |
| PC13-5016-A | EZ-PC13-5016-A       | Single receptacle   | 16 / 3          | 50       | 13   | 36         | 8 1/2 x 14 7/8 x 13 1/2" |
| PC-24-0012A | EZ-PC24-0012-A       | Single receptacle   | 12 / 3          | 100      | 20   | 81         | 10 1/4 x 25 1/2 x 24"    |
| PC13-5012-B | EZ-PC13-5012-B       | Quad receptacle     | 12 / 3          | 50       | 20   | 41         | 8 1/2 x 14 7/8 x 13 1/2" |
| PC-24-0012B | EZ-PC24-0012-B       | Quad receptacle     | 12 / 3          | 100      | 20   | 84         | 10 1/4 x 25 1/2 x 24"    |
| PC13-5012-F | EZ-PC13-5012-F       | G.F.C.I. receptacle | 16 / 3          | 50       | 13   | 38         | 8 1/2 x 14 7/8 x 13 1/2" |



## P-W & SHW SERIES

- External fluid path with 90° full-flow dual ported brass swivel offering both connections from the same side of the reel
- Single pedestal reel with space saving design facilitates workplace organization
- Available in "T" Grade welding hose

| MODEL      | EZ-Coil® Safety Line | I.D. | FT. | PSI | APRX. LBS. | W x H x L                 |
|------------|----------------------|------|-----|-----|------------|---------------------------|
| P-W-125    | EZ-P-W-125           | 1/4" | 25  | 200 | 46         | 8 1/2 x 18 3/8 x 17"      |
| SHW-N-150  | EZ-SHW-150           | 1/4" | 50  | 200 | 64         | 10 1/4 x 21 1/4 x 19 1/2" |
| SHW-N-1100 | EZ-SHW-1100          | 1/4" | 100 | 200 | 84         | 10 1/4 x 25 1/2 x 19 1/2" |



## CM & DM SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE
- CM: Caddy Mount Hand Crank Hose Reel
- DM: Dolly Mount Hand Crank Hose Reel

| MODEL        | I.D. | FT. | PSI   | APRX. LBS. | W x H x L                 |
|--------------|------|-----|-------|------------|---------------------------|
| 112-3-100-CM | 3/8" | 100 | 4,000 | 18         | 18 1/2 x 14 3/4 x 13 1/8" |
| 112-3-150-CM | 3/8" | 150 | 4,000 | 22         | 23 x 14 3/4 x 13 1/8"     |
| 117-4-225-CM | 1/2" | 225 | 4,000 | 28         | 23 x 18 1/2 x 18"         |
| 117-3-200-DM | 3/8" | 200 | 4,000 | 37         | 19 x 36 1/4 x 21"         |
| 117-4-225-DM | 1/2" | 225 | 4,000 | 39         | 23 1/2 x 36 1/4 x 21"     |



## V100 SERIES

- Direct hand crank reel with solid one piece steel "U" shaped frame
- Direct connect port for vacuum hose with bullet cuffs
- Adjustable tension brake to prevent "free-wheeling" during operation, transport or storage

| MODEL     | DESCRIPTION               | VACUUM      |      |        | AIR   |      | APRX. LBS. | W x H x L         |
|-----------|---------------------------|-------------|------|--------|-------|------|------------|-------------------|
|           |                           | INLET       | CAP. | VAC.   | INLET | CAP. |            |                   |
| V-117-850 | Vacuum only, Direct Crank | 1 1/2" Cuff | 50   | 29" Hg | -     | -    | 28         | 23 3/8 x 18 x 17" |



## 1175 SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: AFLAS
- Exclusive low profile outlet riser, open drum slot design for flat smooth hose wrap. All welded steel "A" frame construction for superior reel structure

| MODEL      | MOTOR OPTION                     | I.D. | O.D.    | FT. | PSI   | APRX. LBS. | W x H x L             |
|------------|----------------------------------|------|---------|-----|-------|------------|-----------------------|
| 1175-6-50  | Electric Motor Options Available | 1"   | 1 7/16" | 50  | 3,000 | 67         | 24 1/8 x 26 1/8 x 24" |
| 1175-6-100 |                                  | 1"   | 1 7/16" | 100 | 3,000 | 70         | 28 1/8 x 26 1/8 x 24" |
| 1175-6-150 |                                  | 1"   | 1 7/16" | 150 | 3,000 | 75         | 32 1/8 x 26 1/8 x 24" |
| 1175-6-200 |                                  | 1"   | 1 7/16" | 200 | 3,000 | 83         | 36 3/8 x 26 1/8 x 24" |

### CHOICE OF MOTORS



This selection only represents a sample of products applicable in this industry. Please visit us online or consult the factory for more product options.