



OUR MISSION

WE WILL LEAD THE INDUSTRY IN QUALITY & INNOVATION

We know that there can be no compromise when you live the philosophy of building the best! Every decision regarding our product design is made with one unwavering goal...



TO MAKE THE REQUIRED PRODUCT THE VERY BEST IT CAN BE.

YOUR REEL SOURCE

A HIGHER LEVEL OF STANDARDS



CPCT™ POWDER COAT

Our blue powder coat finish that is long lasting, chip resistant & rust inhibiting



BRASS SWIVEL

External fluid path, machined from solid brass, full flow, swivel for simple seal maintenance



STEEL AXLE

25 mm solid steel axle and lubricated bearings for extra strength & durability. Not a hollow tube & no fluid travels through it



CNC SPUN DISCS

All steel rolled edges & ribbed discs for added safety, strength & durability



CARTRIDGE MOTOR

Enclosed factory tuned & matched cartridge style motor for safe & easy replacement



EZ-COIL® SERIES

A patented safety system that retracts up to 80% slower than conventional reels



SPRING DRIVEN REELS OVERVIEW

	MATERIAL	LENGTH	MAX
GENERAL:	Hose I.D. 6 mm - 32 mm	5 m - 30 m	21 - 345 BAR
FUEL:	Hose I.D. 13 mm - 25 mm	8 m - 23 m	21 BAR
WELDING HOSE:	Hose I.D. 6 mm	8 m - 30 m	14 BAR
WELDING CABLE:	Cable: 13.3 mm ² - 67.4 mm ²	8 m - 15 m	75 AMPS - 450 AMPS

	MATERIAL	LENGTH	MAX
ELECTRICAL:	Cord: 5.26 mm ² - 1.31 mm ²	9 m - 30 m	13 - 35 AMPS
STATIC DISCHARGE:	Cable Size: 4 mm	11 m - 30 m	50 - 100 AMPS
VACUUM:	Hose I.D. 38 mm	8 m	737 mm Hg

