DUAL PURPOSE HOSE REELS - AIR/ELECTRIC **CSERIES**

COXREELS® C Series "Combination" spring driven air hose/electric cord reels are two reels in one compact assembly. They are perfect for applications that require pneumatic air and an electrical power feed. The single expanded mounting base creates stability and adds to the convenience of one mounting pattern. This series is also available in dual hose combinations.


FOR INDOOR USE ONLY

Coxreels electric and pneumatic hose reels operate as two independent, self-retracting 50 foot trouble-free assemblies. All models rated: 115 volts, 3* conductors, 60 hz single phase.

All models rated: 115 volts, 3° conductors, 60 nz single phase. HOSE & CORD											
MODEL	ACCESSORY	AWG / NO COND.	CORD FT.	TYPE	AMPS.	I.D.	0.D.	FT.	PSI	APRX. LBS.	Size Index
C-L350-5016-A	Single Industrial Receptacle [†]	16 / 3	50	SJ0	13	³ ⁄8"	5⁄8"	50	300	94	1
C-L350-5012-A		12 / 3	50	SJ0	20	3⁄8"	5⁄8"	50	300	96	1
C-L350-5012-B	Quad "4 Plug" Industrial Receptacle [†]	12 / 3	50	SJ0	20	3⁄8"	5⁄8"	50	300	97	1
C-L350-5016-C	Fluorescent Tube Light - Shock Absorbing & Shatter Resistant [†]	16 / 3	50	SJT0	.3	3⁄8"	5⁄8"	50	300	94	1
C-L350-5016-D	Fluorescent Angle Light with Tool Tap Plug [†]	16 / 3	50	SJT0	13	3⁄8"	5⁄8"	50	300	94	1
C-L350-5016-D2	Dual Fluorescent Angle Light with Tool Tap Plug [†]	16 / 3	50	SJTO	12	3⁄8"	5⁄8"	50	300	94	1
C-L350-5016-E	Incandescent Caged Drop Light with Tool Tap Plug [†]	16 / 3	50	SJT0	13	3⁄8"	5⁄8"	50	300	94	1
C-L350-5016-F	Duplex G.F.C.I. Metal Industrial Receptacle [†]	16 / 3	50	SJ0	13	3⁄8"	5⁄8"	50	300	94	1
C-L350-5012-F	-	12 / 3	50	SJ0	20	³ ⁄8"	5⁄8"	50	300	96	1
C-L350-5016-X	With Hose, With Cord, Less Accessory	16 / 3	50	SJ0	13	3⁄8"	5⁄8"	50	300	93	1
C-L350-5012-X	V	12 / 3	50	SJ0	20	3⁄8"	5⁄8"	50	300	95	1
C-L350L-5016L-X	Less Hose, Less Cord.	16 / 3	50	N/A	25	3⁄8"	5⁄8"	50	300	78	1
C-L350L-5012L-X	Less Cord, Less Accessory	12 / 3	50	N/A	25	3⁄8"	5⁄8"	50	300	78	1

REEL DIMENSIONS Technical Data Sheets Available On Website

SIZE INDEX	w	н	L	Х	Y	М	Ν	
1	16"	185⁄8"	17"	8"	9"	7"	8"	
	(verall Dimension		Bo Bo		Mounting Pattern		



Listed[†] :: Accessories only

- SWIVEL & LEAD CABLE
 - \bullet External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
 - Swivel Seals: NITRILE
 - External CPC[™] powder coated steel components cover for simple slip ring routine maintenance

C SERIES :: REEL SPECIFICATIONS

· Include 5' lead cable & grounding plug (except on less cord models)

DESIGN & STRUCTURE

- Compact two reel assembly for air/electric applications, each reel operates independently
- Guide arm adjusts to wall, floor & overhead positions
- Single expanded, 1/4" steel mounting base for increased stability & space efficiency
- One mounting pattern allow 1/2 the installation time required to install 2 reels at one station
- 1" solid steel axle & lubricated precision bearings for smooth rotation

RETRACTION

- Enclosed factory tuned & matched cartridge-style spring motor
- Non corrosive stainless steel spring, pawl & zinc plated ratchet
- \bullet Multi-position lock ratchet mechanism secures hose/cord at desired length

SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC[™] powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Air Services
- Pneumatic Tools
- Power Tools
- Light Source
- General Industrial

ACCESSORIZE YOUR REEL .: PG 50 🕏

- 0-Rings & Swivels
- Mounting Brackets
- Hoses
 Assorted Reel Accessories

 Manufacturing Plants & Facilities

Maintenance, Repair

Automotive & Fleet

Service Centers

& Operations

