# SS SERIES

# STAINLESS STEEL SPRING RETRACTABLE HOSE REELS



# SS SERIES - SPRING :: REEL SPECIFICATIONS

- · Non-corrosive external fluid path with machined from high quality stainless steel 90° full-flow NPT swivel inlet
- · Swivel Seals: NITRILE Non-Toxic Food Grade Grease

#### DESIGN & STRUCTURE

- · Electro-polished stainless steel finish
- · Each of these reels is built of their standard series with their own unique features & benefits

- · See page 11 For P Series spring driven features
- · See page 12 For SH & MP Series spring driven features
- · See page 13 For T Series spring driven features
- · See page 16 For EN Series spring driven features

#### SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC<sup>™</sup> powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

#### POSSIBLE FIELDS OF APPLICATION

- · Corrosive Environments
- · Hygienic Environments
- · Medical Services
- · Marine/Docks/Offshore
- · Manufacturing Plants & Facilities
- · Pulp & Paper Plants
- · Food & Chemical **Processing Plants**
- · Bottling Plants

- Dairies
- · Meat Packing
- · Grocery Stores
- · Restaurants & Commercial Kitchens
- Water Treatment & Supply
- Petrochemical
- · Food Grade Washdown

## ACCESSORIZE YOUR REEL :: PG 50

- 0-Rings & Swivels
- · Mounting Brackets
- Hoses
- Assorted Reel Accessories

**COXREELS®** SS Series "Stainless Steel" spring drivenhose reels have similar features to their related series, but are constructed of high quality electro-polished stainless steel with stainless steel fluid paths. They offer clean, non-corrosive performance in applications that require it, such as food and chemical processing, marinas, and anywhere that rust, corrosion and contamination thrive.

#### **PSERIES**-Spring Rewind

LESS HOSE						
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	SIZE INDEX
P-LPL-335-SS	3/8"	21/32"	35	300	34	1
P-LPL-350-SS	3/8"	21/32"	50	300	39	1
P-LPL-425-SS	1/2"	21/32"	25	300	39	2

### SH, & MP SERIES -Spring Rewind

LESS HOSE						
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	SIZE
SHL-N-350-SS	3/8"	21/32"	50	300	44	3
SHL-N-450-SS	1/2"	27/32"	50	300	46	3
SHL-N-525-SS	3/4"	15/32"	25	300	45	4
MPL-N-350-SS	3/8"	5/8"	50	3000	53	3
MPL-N-450-SS	1/2"	3/4"	50	2500	53	3

## **TSERIES**-Spring Rewind

LESS HOSE						
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	SIZE
TSHL-N-4100-SS	1/2"	27/32"	100	300	80	5
TSHL-N-550-SS	3/4"	15⁄32"	50	300	70	6

# **EN SERIES** -Spring Rewind

LESS HOSE						SIZE
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	INDEX
ENL-N-335-SS	3/8"	21/32"	35	300	46	7
ENL-N-350-SS	3/8"	21/32"	50	300	58	8
ENL-N-450-SS	1/2"	27/32"	50	300	61	8

# **REEL DIMENSIONS** Technical Data Sheets Available On Website

SIZE INDEX	W	н	L	Х	Y	М	N
1	63/4"	185⁄8"	17 <sup>1</sup> /8"	6"	6"	4"	5"
2	7"	185⁄8"	171/8"	6"	6"	4"	5"
3	81/4"	211/4"	191/2"	6"	6"	4"	5"
4	93/8"	211/4"	191/2"	6"	6"	4"	5"
5	93/8"	251/2"	24"	8"	9"	7"	8"
6	97/8"	251/2"	24"	8"	9"	7"	8"
7	67/8"	187⁄8"	19"	6"	6"	4"	5"
8	81/2"	213/4"	217⁄8"	6"	6"	4"	5"
	Overall Dimensions			Ba	ise —	Mountin	g Pattern —



