
100 SERIES COMPACT HAND CRANK HOSE REELS



100 SERIES :: REEL SPECIFICATIONS

SWIVEL

- \bullet External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Up to 4,000 PSI working pressure
- Swivel Seals: NITRILE

DESIGN & STRUCTURE

- · Professional grade, compact & lightweight design
- ${\boldsymbol{\cdot}}$ Open drum design for no hassle hose wrap
- Solid one piece, heavy gauge steel "U" shaped frame
- Adjustable tension brake to prevent "free-wheeling" during operation, transport or storage

RETRACTION

Direct hand crank rewind

SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary $\mathsf{CPC^{\mathsf{TM}}}$ powder coat process
- Rolled edges & ribbed discs provide strength & safety

Farming

Hoses

· Construction Sites

Home Gardening

 General Landscape/ Turf Care

- Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Water Supply
- Washdown
- Pressure Washing
- Agricultural Spraying
- Chemical Fluid Transfer
- Ground Maintenance

ACCESSORIZE YOUR REEL .: PG 50

- O-Rings & Swivels
- Assorted Reel Accessories

COXREELS® 100 Series hand crank hose reels are lightweight, compact, versatile reels that perform at working pressures up to 4,000 PSI. Save time and effort while increasing the safety of your work environment. The sturdy "U" shaped frame and all steel construction make this one tough little reel. All listed models are supplied less hose. Stainless steel models are available.

100 SERIES MODELS

	LESS HOSE									
	MODEL	STANDARD CAPACITY			OPTIONAL CAPACITY Reducer Required			PSI	APRX LBS.	SIZE INDEX
		I.D.	0.D.	FT.	I.D.	0.D.	FT.		LDJ.	
	112-3-50	3⁄8"	5⁄8"	50	1⁄4"	1⁄2"	85	4,000	15	1
	112-3-100	3⁄8"	5⁄8"	100	1⁄4"	1⁄2"	150	4,000	19	2
	112-3-150	3⁄8"	5⁄8"	150	1/4"	1⁄2"	225	4,000	21	3
	117-3-250	3⁄8"	⁵ ⁄8"	250	1⁄4"	1⁄2"	350	4,000	30	4
	117-3-400	3⁄8"	5⁄8"	400	1⁄4"	1⁄2"	550	4,000	33	5
	117-3-550	3⁄8"	⁵ ⁄8"	550	1⁄4"	1⁄2"	800	4,000	35	6
	112-4-75	1⁄2"	7⁄8"	75	3⁄8"	3⁄4"	100	4,000	21	3
	117-4-225	1⁄2"	7⁄8"	225	3⁄8"	3⁄4"	315	4,000	31	5
[117-4-350	1⁄2"	7⁄8"	350	3⁄8"	³ ⁄4"	450	4,000	37	6
	117-5-100	3⁄4"	11⁄4"	100	1⁄2"	1"	150	4,000	35	7

REEL DIMENSIONS Technical Data Sheets Available On Website

SIZE INDEX	w	H	L	Х	Y	М	N	Ø	Dw
1	14½"	13"	12"	6"	6"	4"	3"	51⁄2"	41/2"
2	18¼/4"	13"	12"	91⁄2"	6"	51⁄2"	3"	51⁄2"	8"
3	22 ³ ⁄4"	13"	12"	14"	6"	10"	3"	5 ¹ ⁄2"	12 ¹ ⁄2"
4	18¼/4"	18"	17"	91⁄2"	6"	51⁄2"	3"	51⁄2"	8"
5	22 ³ ⁄4"	18"	17"	14"	6"	10"	3"	5 ¹ ⁄2"	12½"
6	28 ¹ /4"	18"	17"	19½"	6"	15½"	3"	51⁄2"	18"
7	23 ¹ /4"	18"	17"	14"	6"	10"	3"	51⁄2"	12½"
Overall Dimensions				Ba	ise	Mounting Pattern		Drum — Drum	

